

Safety

1. To prevent possible hearing damage, do not listen at high volume levels for long periods.
2. Risk of explosion if battery is replaced by an incorrect type, dispose of battery according to the instruction.
3. Recycle your products
The WEEE logo (shown at right) appears on the product to indicate that this product must not be disposed of or dumped with your other household wastes. You are liable to dispose of all your electronic or electrical waste equipment by transporting to an appropriate collection point for recycling of such hazardous waste.



FCC Radiation Exposure Statement: This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

IC Warning:

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en

IC Radiation Exposure Statement:

This equipment complies with IC RSS-102 radiation exposure limits set forth for an uncontrolled environment. This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

FCC Notice

This device complies with Part 15 of FCC rules. Operation is subject to the following 2 conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



www.eartec.com

1.800.399.5994

Dimensions	2.4"w x 1.5"d x 4"h
Maximum Deviation	< +5KHz
Weight	5 oz
Spurious Radiation Modulation	< -60dB
Frequency Stability	+/- 5ppm
Frequency Range	UHF 462+467.7125 MHz
Channels	14 FRS CH
CTCSS	38 Tones
Operating Voltage	7.2V
Receiving Stability	< 0.2uV
Operating Temp.	-30 to 60 C
Operating Mode	Simplex
Output Power	0.5W
Radio Power Supply	Rechargeable Lithium Battery
Operation Time	10 Hours
Antenna	Fixed
FCC License	None Required



Scrambler UHF